



# Twin Pedestal Wallbox Series

### Innovativeness

One charger with two output sockets  
Business use with intelligent App control  
Vandal resistant and anti-corrosion

### Intelligent Control

Ethernet/4G/Wi-Fi communication all supported  
OCPP communication protocol with CMS ent  
Intelligent operation by App and cashless payment

### Flexible Option

App operation or RFID authentication or plug and play  
Customization with different color painting



Model	ZECO14K-T1	ZECO22K-T2	ZECO44K-T3
<b>Technical features</b>			
Charging capacity	Up to 14KW(7KW*2)	Up to 22KW(11KW*2)	Up to 44KW(22KW*2)
Input/Output power	230VAC±20%-50/60Hz-32A*2-1phase	400VAC±20%-50/60Hz-16A*2-3phase	400VAC±20%-50/60Hz-32A*2-3phase
RCD	RCMU(Type A+ DC 6mA)/ Type B RCCB(Optional).		
Standby power	<5W		
Measuring accuracy	1%		
Energy Meter	MID certified		
OCPP	OCPP1.6 Json(OCPP2.0 optional)		
Communication	WIFI/Ethernet/4G(Optional)		
User interface	LCD 5 inch Touch Screen/ RFID(mifare iso& IEC 14443A)		
Certificate/Compliance	CE/FCC/ROHS/REACH/IEC/EN 61851-1 , IEC/EN61851-21-2, IEC/EN 62955, EN300328, EN 301489-1/-17,EN62479.		
Charging Interface	Type 2 socket*2 or Type 2 Gun *2 5M		
Special Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection		
<b>Physical properties</b>			
Warranty	2 years		
Protection	IP65, IK10,		
Enclosure	Galvanized steel		
Front Panel	Temper glass		
Installation	Wall-mount/Pole-mount.		
Cooling	Natural cooling		
Operating temperature	-30°C to +55°C		
Humidity	Max.95%(non-regulating)		
Product Dimensions	503*334*155(L*W*H)mm		
Package Dimension	610*415*250(L*W*H)mm		
Net Weight	13.5Kg	13.5Kg	13.5Kg
Gross Weight	15Kg	15Kg	15Kg